

## SIRUI S-N SERIES **PROFESSIONAL TRIPODS**

S-N **Series** 

S-N series flat style tripods have an extremely functional appearance, are only 1.6 inches (4 cm) thick when folded flat and are small enough to be easily carried and stored in a suitcase or backpack. All S-N series tripods have 8 layer carbon fiber legs for maximum load handling and light weight.



Flat design makes it easy to carry and store in backpacks and carry-ons.

For added load capacity and stability, this new Flat design + versatility = perfect generation of flat style tripods has increased choice for travel photography minimum leg tube diameters. The reversible center column lets you mount your camera at a unique angle for low level or ground level shooting S-N 2 Series tripods have retractable stainless

steel spikes for outdoor photography.

S-1204N Recommended Ball Heads:

S-1205N Recommended Ball Heads: K-10X, G-10X


S-2204N Recommended Ball Heads:

S-2205N Recommended Ball Heads: K-20X, G-20X

The hook at the bottom of the center column allows you to hang additional weight (sand bag, camera bag, etc.) under the tripod for added stability.

## Newly designed locking system

The SIRUI S-N series tripod has a unique leg position locking system that clicks in place when the tripod is opened. This guarantees that the tripod legs will be properly positioned - providing a rugged, stable support for your equipment. Simply open the tripod in the direction of the arrows until it clicks into place. When you're done shooting, press the red unlock button and close the tripod flat.



## What's included:

Short center column, custom case, padded shoulder strap, tools, instruction manual, warranty card

## S-N SERIES TRIPODS

| BSRS1204 S1204N Carbon Fiber 4 25 16 6.9 (175) 45.1 (1145) 54.1 (1375) 18.5 (470) 59.6 (1515) 15.3 (390) 2.4 (1.1) 26.4 (12) \$578 BSRS1205 S1205N Carbon Fiber 5 25 13 6.7 (170) 47.2 (1200) 55.5 (1410) 17.7 (450) 60.6 (1540) 14.3 (365) 2.4 (1.1) 26.4 (12) \$680 BSRS2204 S2204N Carbon Fiber 4 28 19 6.9 (175) 45.5 (1155) 54.1 (1375) 18.9 (480) 59.8 (1520) 15.7 (400) 3.1 (1.4) 33 (15) \$680 BSRS2204 S2204N Carbon Fiber 4 28 19 6.9 (175) 45.5 (1155) 54.1 (1375) 18.9 (480) 59.8 (1520) 15.7 (400) 3.1 (1.4) 33 (15)   | • • • • • • • • |         | 0 = 0        |       | Max  | Min  |           |             |             |            | Mono        | Mono Min   |           |           |          |  |
|---|-----------------|---------|--------------|-------|------|------|-----------|-------------|-------------|------------|-------------|------------|-----------|-----------|----------|--|
| BSRS1204 S1204N Carbon Fiber 4 25 16 6.9 (175) 45.1 (1145) 54.1 (1375) 18.5 (470) 59.6 (1515) 15.3 (390) 2.4 (1.1) 26.4 (12) \$578 BSRS1205 S1205N Carbon Fiber 5 25 13 6.7 (170) 47.2 (1200) 55.5 (1410) 17.7 (450) 60.6 (1540) 14.3 (365) 2.4 (1.1) 26.4 (12) \$680 BSRS2204 S2204N Carbon Fiber 4 28 19 6.9 (175) 45.5 (1155) 54.1 (1375) 18.9 (480) 59.8 (1520) 15.7 (400) 3.1 (1.4) 33 (15) \$680 BSRS2204 S2204N Carbon Fiber 4 28 19 6.9 (175) 45.5 (1155) 54.1 (1375) 18.9 (480) 59.8 (1520) 15.7 (400) 3.1 (1.4) 33 (15) \$680 BSRS2204 S2204N Carbon Fiber 4 28 19 6.9 (175) 45.5 (1155) 54.1 (1375) 18.9 (480) 59.8 (1520) 15.7 (400) 3.1 (1.4) 33 (15) \$680 BSRS2204 S2204N Carbon Fiber 4 28 19 6.9 (175) 45.5 (1155) 54.1 (1375) 18.9 (480) 59.8 (1520) 15.7 (400) 3.1 (1.4) 33 (15) \$680 BSRS2204 S2204N Carbon Fiber 4 28 19 6.9 (175) 45.5 (1155) 54.1 (1375) 18.9 (480) 59.8 (1520) 15.7 (400) 3.1 (1.4) 33 (15) \$680 BSRS2204 S2204N Carbon Fiber 4 28 19 6.9 (175) 45.5 (1155) 54.1 (1375) 18.9 (480) 59.8 (1520) 15.7 (400) 3.1 (1.4) 33 (15) \$680 BSRS2204 S2204N Carbon Fiber 4 28 19 6.9 (175) 45.5 (1155) 54.1 (1375) 18.9 (480) 59.8 (1520) 15.7 (400) 3.1 (1.4) 33 (15) \$680 BSRS2204 S2204N Carbon Fiber 4 28 19 6.9 (175) 45.5 (1155) 54.1 (1375) 18.9 (480) 59.8 (1520) 15.7 (400) 3.1 (1.4) 33 (15) \$680 BSRS2204 S2204N Carbon Fiber 4 28 19 6.9 (175) 45.5 (1155) 54.1 (1375) 18.9 (480) 59.8 (1520) 15.7 (400) 3.1 (1.4) 33 (15) \$680 BSRS2204 S2204N CARBON FIBER 5 (1150) 18.9 (11 |                 | Sirui   |              | # of  | Leg  | Leg  | Min Ht    | Max Ht      | Max Ht Ext  | Retract Ht | Max Ht      | Ht         | Weight    | Load      |          |  |
| BSRS1205 S1205N Carbon Fiber 5 25 13 6.7 (170) 47.2 (1200) 55.5 (1410) 17.7 (450) 60.6 (1540) 14.3 (365) 2.4 (1.1) 26.4 (12) \$60 BSRS2204 S2204N Carbon Fiber 4 28 19 6.9 (175) 45.5 (1155) 54.1 (1375) 18.9 (480) 59.8 (1520) 15.7 (400) 3.1 (1.4) 33 (15) \$60 BSRS2204 S2204N Carbon Fiber 4 28 19 6.9 (175) 45.5 (1155) 54.1 (1375) 18.9 (480) 59.8 (1520) 15.7 (400) 3.1 (1.4) 33 (15)  | Item #          | Model # | Materials    | Sect. | Diam | Diam | in (mm)   | in (mm)     | in (mm)     | in (mm)    | in (mm)     | in (mm)    | lb (kg)   | lb (kg)   | MSRP     |  |
| BSRS2204 S2204N Carbon Fiber 4 28 19 6.9 (175) 45.5 (1155) 54.1 (1375) 18.9 (480) 59.8 (1520) 15.7 (400) 3.1 (1.4) 33 (15) \$60   | BSRS1204        | S1204N  | Carbon Fiber | 4     | 25   | 16   | 6.9 (175) | 45.1 (1145) | 54.1 (1375) | 18.5 (470) | 59.6 (1515) | 15.3 (390) | 2.4 (1.1) | 26.4 (12) | \$570.95 |  |
|   | BSRS1205        | S1205N  | Carbon Fiber | 5     | 25   | 13   | 6.7 (170) | 47.2 (1200) | 55.5 (1410) | 17.7 (450) | 60.6 (1540) | 14.3 (365) | 2.4 (1.1) | 26.4 (12) | \$604.95 |  |
| BSRS2205 S2205N Carbon Fiber 5 28 16 7.1 (180) 47.8 (1215) 53.9 (1370) 17.7 (450) 60.2 (1530) 14.5 (370) 3.1 (1.4) 26.4 (12) \$63   | BSRS2204        | S2204N  | Carbon Fiber | 4     | 28   | 19   | 6.9 (175) | 45.5 (1155) | 54.1 (1375) | 18.9 (480) | 59.8 (1520) | 15.7 (400) | 3.1 (1.4) | 33 (15)   | \$604.95 |  |
|   | BSRS2205        | S2205N  | Carbon Fiber | 5     | 28   | 16   | 7.1 (180) | 47.8 (1215) | 53.9 (1370) | 17.7 (450) | 60.2 (1530) | 14.5 (370) | 3.1 (1.4) | 26.4 (12) | \$639.95 |  |



added

S-N tripods excellent for travel photography.

series

tripods

with a detachable

versatility,

designed

leg

are

Address: 111 Asia Place, Carlstadt, NJ 07072

Phone: 201.939.7722

